

# Doctor Blades

Quality and Technology

## GlassHT 230

Fiber Glass

### Specification sheet for GlassHT 230

- Superfine cotton fiber composite, with glass fiber bonded by an epoxy-resin
- Color: Natural – Brown
- Bending strength: Min 250 N/mm<sup>2</sup>
- Temperature resistance: 260°C
- Chemical resistance: Very good
- Water Absorption: Very low
- Standard dimension (\*):

Thickness - mm (inch): 1,5 (0,060) 1,9 (0,075) 2,3 (0,090) 2,8 (0,110)

Width 1 - mm (inch): 50 (2) 50 (2) 50 (2) 50 (2)

Width 2 - mm (inch): 75 (3) 75 (3) 75 (3) 75 (3)

\*Other widths and thickness are tailor made available.


Riveting: Supplied with rivets, packers, rings, washers and clips. Profiles to suit all holder systems.

### Applications:

- \*Calander (Steel)
- \* Soft Calander
- \* Dryer Cylinder
- \* Dryer Cylinder Coater
- \* MG Cylinder
- \* Pope Reel

### Key features:

- Continuous length to individual specification;
- Single or double bevel from 15° to 90°;
- Rebate or groove;
- Available as parts under special design.



**RollDoctor**  
Doctor Blades  
RAFFAI RIDGES

Advanced Solutions for each special Customer's requirement.

We Provide Technology

