



RollDoctor
GROUP
DOCTOR BLADES

Doctor Blades

Quality and Technology

RollGlassRED

- High Bend Strength

Specification sheet for ROLLGLASS RED

- Ultrafine composite glass fiber bonded with an special epoxy-resin. High bend strength
- Color: Red /Green
- Bending strength: Min 600 N/mm²
- Temperature resistance: up to 200°C
- Chemical resistance: Very good
- Water Absorption: No
- Standard dimension (*):

Thickness - mm (inch): 1,5 (0,060) 1,9 (0,075) 2,3 (0,090) 2,8 (0,110)

Width 1 - mm (inch): 50 (2) 50 (2) 50 (2) 50 (2)

Width 2 - mm (inch): 75 (3) 75 (3) 75 (3) 75 (3)

*Other widths and thickness are tailor made available.

Riveting: Supplied with rivets, packers, rings, washers and clips. Profiles to suit all

Applications:

- * Press Roll
- * Drying Cylinder
- * Calander
- * MG Cylinder
- * Pope Reel
- * Size Press

Key features:

- Continuous length to individual specification;
- Single or double bevel from 15° to 90°;
- Rebate or groove;
- Available as parts or pieces under special design.



RollDoctor
Doctor Blades

Advanced Solutions for each special Customer's requirement.

We Provide Technology

